

List of available RTU32 types

July 2006

RTU32 without built-in I/O, 64Mb RAM and Flash and basic driver support (Modbus suite of protocols and utility protocol EN/IEC60870)

UCN-B/121B0110.0	RTU32 Basic without embedded I/O - 2 x RS232 - 115-230VAC/DC
UCN-B/121B0130.0	RTU32 Basic without embedded I/O - 2 x RS232 - 24-48VDC
UCN-B/121B0210.0	RTU32 Basic without embedded I/O - 6 x RS232 - 115-230VAC/DC
UCN-B/121B0230.0	RTU32 Basic without embedded I/O - 6 x RS232 - 24-48VDC
UCN-B/121B0310.0	RTU32 Basic without embedded I/O - 5 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-B/121B0330.0	RTU32 Basic without embedded I/O - 5 x RS232 + 1 x RS485 - 24-48VDC
UCN-B/121B0410.0	RTU32 Basic without embedded I/O - 1 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-B/121B0430.0	RTU32 Basic without embedded I/O - 1 x RS232 + 1 x RS485 - 24-48VDC

RTU32 without built-in I/O, 64Mb RAM and Flash and basic driver support (Modbus suite of protocols and utility protocol EN/IEC60870) Additional STRATON SNMP Agent driver

UCN-B/122B0110.0	RTU32 Basic without embedded I/O - 2 x RS232 - 115-230VAC/DC
UCN-B/122B0130.0	RTU32 Basic without embedded I/O - 2 x RS232 - 24-48VDC
UCN-B/122B0210.0	RTU32 Basic without embedded I/O - 6 x RS232 - 115-230VAC/DC
UCN-B/122B0230.0	RTU32 Basic without embedded I/O - 6 x RS232 - 24-48VDC
UCN-B/122B0310.0	RTU32 Basic without embedded I/O - 5 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-B/122B0330.0	RTU32 Basic without embedded I/O - 5 x RS232 + 1 x RS485 - 24-48VDC
UCN-B/122B0410.0	RTU32 Basic without embedded I/O - 1 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-B/122B0430.0	RTU32 Basic without embedded I/O - 1 x RS232 + 1 x RS485 - 24-48VDC

RTU32 with built-in I/O, 64Mb RAM and Flash and basic driver support (Modbus suite of protocols and utility protocol EN/IEC60870)

UCN-26IOA/121B0110.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 2 x RS232 - 115-230VAC/DC
UCN-26IOA/121B0130.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 2 x RS232 - 24-48VDC
UCN-26IOA/121B0210.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 6 x RS232 - 115-230VAC/DC
UCN-26IOA/121B0230.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 6 x RS232 - 24-48VDC
UCN-26IOA/121B0310.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 5 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-26IOA/121B0330.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 5 x RS232 + 1 x RS485 - 24-48VDC
UCN-26IOA/121B0410.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 1 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-26IOA/121B0430.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 1 x RS232 + 1 x RS485 - 24-48VDC

RTU32 with built-in I/O, 64Mb RAM and Flash and basic driver support (Modbus suite of protocols and utility protocol EN/IEC60870) Additional STRATON SNMP Agent driver

UCN-26IOA/122B0110.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 2 x RS232 - 115-230VAC/DC
UCN-26IOA/122B0130.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 2 x RS232 - 24-48VDC
UCN-26IOA/122B0210.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 6 x RS232 - 115-230VAC/DC
UCN-26IOA/122B0230.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 6 x RS232 - 24-48VDC
UCN-26IOA/122B0310.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 5 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-26IOA/122B0330.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 5 x RS232 + 1 x RS485 - 24-48VDC
UCN-26IOA/122B0410.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 1 x RS232 + 1 x RS485 - 115-230VAC/DC
UCN-26IOA/122B0430.D	RTU32 with 16DI, 4RO, 4AI, 2AO - 1 x RS232 + 1 x RS485 - 24-48VDC