



SPS - 060



SPS - 100



SPU - 150



SPU - 230

**Switch-mode supplies from
60 W to 230 W**

Compact size, low weight

**Universal supply voltage
85 - 265 VAC, 47 - 63 Hz**

Protected against over voltage

Short-circuit and overload protected

Made in accordance with the  and EMC regulations

Type	DC-output	Adjustment	Max. power	Max. current	Max. ripple	Efficiency	Mech. dimensions	Weight
SPS-060-24	24 V	+/- 5%	60W	2,5 A	240 mV	80 %	160 x 95 x 38	485 g
SPS-100-05	5 V	+/- 3%	100W	20 A	70 mV	72 %	199 x 95 x 38	625 g
SPS-100-12	12 V	+/- 3%	100W	8,5 A	120 mV	75 %	199 x 95 x 38	625 g
SPS-100-24	24 V	+/- 3%	100W	4,5 A	240 mV	78 %	199 x 95 x 38	625 g
SPU-150-24	24 V	+/- 5%	150W	6,5 A	240 mV	78 %	197 x 97 x 38	715 g
SPU-230-24	24 V	+/- 2%	230W	9,5 A	200 mV	72 %	203 x 114 x 50	1050 g

The above mentioned types are kept in stock in Denmark

Power supplies with 2, 3 or 4 different outputs are available on request.