

**Battery Charger,
DCP2-1205**



**Battery Charger,
DCP2-2405**



**Battery Charger,
DCP2-1210**



Main function:	The DCP2 can be applied as battery charger or as a universal DC voltage supply.		
Input voltage:	1 x 230V AC $\pm 15\%$ 47...63Hz	1 x 230V AC $\pm 15\%$ 47...63Hz	1 x 230V AC $\pm 15\%$ 47...63Hz
Output voltage:	12V DC (adjustable 11.8...13.8V DC)	24V DC (adjustable 23.5...27.5V DC)	12V DC (adjustable 11.8...13.8V DC)
Output current:	5A (typical current limit 6A)	5A (typical current limit 6A)	10A (typical current limit 12.5A)
Protection:	IP20	IP20	IP20
Size:	147 x 123 x 86 mm	147 x 123 x 86 mm	205 x 123 x 86 mm
Weight:	approx. 0.8 kg	approx. 0.8 kg	approx. 1.2 kg

**Battery Charger,
DCP2-2410**



**Battery Charger,
DCP2-2420**



**Battery Charger,
DCP2-2420**



Main function:	The DCP2 can be applied as battery charger or as a universal DC voltage supply.		
Input voltage:	1 x 230V AC $\pm 15\%$ 47...63Hz	1 x 230V AC $\pm 15\%$ 47...63Hz	3 x 400/480V AC $\pm 15\%$ 47...63Hz
Output voltage:	24V DC (adjustable 23.5...27.5V DC)	24V DC (adjustable 23.5...27.5V DC)	24V DC (adjustable 23.5...27.5V DC)
Output current:	10A (typical current limit 12.5A)	20A (typical current limit 25A)	20A (typical current limit 25A)
Protection:	IP20	IP20	IP20
Size:	205 x 123 x 86 mm	240 x 153 x 86 mm	240 x 153 x 86 mm
Weight:	approx. 1.2 kg	approx. 1.9 kg	approx. 1.9 kg

Battery Charger, DCP2-2440



Main function:

The DCP2 can be applied as battery charger or as a universal DC voltage supply.

Input voltage:

3 x 400/480V AC $\pm 15\%$
47...63Hz

Output voltage:

24V DC
(adjustable 23.5...27.5V DC)

Output current:

40A (typical current limit 45A)

Protection:

IP20

Size:

292 x 185 x 130 mm

Weight:

approx. 3.6 kg